



Urethane Seam Sealer

08362 • 08365 • 08367 • 08368

Technical Data Sheet

June, 2013

3M Part No.(s)	3M Part Descriptor(s)
08362	3M™ Urethane Seam Sealer - Grey
08365	3M™ Urethane Seam Sealer - Beige
08367	3M™ Urethane Seam Sealer - Black
08368	3M™ Urethane Seam Sealer - White

Product Description 3M™ Urethane Seam Sealer is a high performance general purpose seam sealer ideal for sealing both interior and exterior joints of primer and paint coated substrates.

Features

- High Solids, Single Component, Moisture curing
- No Shrinkage, No / Low Odor
- Standard 10.5 fl. oz. / 310 mL Aluminum Cartridge

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Container	10.5 fl. oz. / 310 mL Aluminum Cartridge
Base	Moisture-curing urethane
Density	9.8 lb/gal
Color	08362 (Grey), 08365 (Beige), 08367 (Black), 08368 (White)
Flash Point	92°F (Closed Cup Method)
Solids Content	95%
Consistency	Heavy Paste
Solvent	Minimal amount of Xylene
Service Temperature	-25 to 180°F

3M™ Urethane Seam Sealer

08362 • 08365 • 08367 • 08368

Product Uses

3M™ Urethane Seam Sealer is an excellent choice when sealing seams to help prevent the intrusion of water, dust, and air, aiding in providing corrosion resistance at these locations. 3M™ Urethane Seam Sealers provide excellent gap filling properties and are designed to be used over epoxy or urethane based primers they should be top coated when exposed to ultra violet rays.

Use with the following accessories:

- 3M™ Single Component Cartridge Applicator Gun (PN 08990)
- 3M™ Professional Manual Caulking Gun (PN 08993)
- 3M™ Threaded Cartridge Nozzles (PN 08187) 50/box

Typical Performance Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Cold Temperature Resistance @ -20°F	(Remains Flexible)
Heat Resistance - 8 Weeks @ 200°F	(No Degradation)
Adhesion - Primed Metal: Excellent	(Cohesive Failure)
Bare Metal: Excellent	(Cohesive Failure)
Tensile Strength: Good	(230 psi)
Flexibility: Excellent	(600% Elongation)

Directions for Use

NOTE: 3M Best Practice is that all sealers, unless designated specifically for use on bare metal, be applied to properly prepared paint or primer designed for the specific application. Applying over bare metal will not provide adequate corrosion protection.

Acid etch primer is not recommended to be used in direct contact with any 3M seam sealer. Residual acid can weaken the bond.

1. Lightly scuff the coated area where the sealer is to be applied using a 3M™ Scotch-Brite™ scuff pad (PN 07447).
2. Clean with an appropriate VOC compliant cleaner product for removal of surface contaminants. Reference the 3M Automotive Aftermarket Catalog for a suitable VOC compliant product for your area.
3. Perforate the seal at the cartridge outlet and install the nozzle. Use the pull tab to remove the metal seal at the cartridge base. Install the cartridge in a suitable caulking gun (see reference in “Product Uses” section).
4. Cut nozzle to provide desired bead size.
5. Apply seam sealer and tool (if necessary) to desired finished appearance (use water or mild solvent such as a pre-cleaner to tool). Do not tool with any alcohol containing solvents, they will stop the curing process of the seam sealer.
6. Wait at least 30 minutes before painting (1/4" bead at 70°F, 50% humidity), for thicker beads, lower temperatures, or lower humidity, allow additional time before painting.

3M™ Urethane Seam Sealer

08362 • 08365 • 08367 • 08368

Applications	Sealing of seams to prevent intrusion of water, dust, air, fumes, may be used for interior or exterior seams of primer coated substrates.
Storage and Handling	Store at room temperature. Rotate stock on a “first-in-first-out” basis. When stored at the recommended conditions in original, unopened containers, this product has a shelf life of 12 months. Use in a well-ventilated area.
Precautionary Information	Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.
Technical Information	The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.
Product Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.
Warranty, Limited Remedy, and Disclaimer	Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

For Additional Health and Safety Information



Automotive Aftermarket Division

3M Center, Building 223-6N-01
St. Paul, MN 55144-1000
1-877-666-2277 (1-877-MMM-CARS)
www.3MCollision.com

3M and Scotch-Brite are trademarks of 3M Company.
Printed in U.S.A.
©3M 2013 All rights reserved. (6/13)

This is the last page