Page: 1

Revision: 03/06/2019

This SDS complies with the Canadian Hazardous Products Regulations of 2015.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code:

KSA3900

Product Name:

Aircraft Aerosol Non MeCl

Company Name:

W. M. Barr

Phone Number:

2105 Channel Avenue

(901)775-0100

Memphis, TN 38113

Web site address:

www.wmbarr.com

Emergency Contact:

3E 24 Hour Emergency Contact

(800)451-8346

Information:

W.M. Barr Customer Service

(800)398-3892

Intended Use:

Paint/Varnish Remover

Product Code:

EAR2000

2. HAZARDS IDENTIFICATION

Flammable Gases, Category 2

Gas Under Pressure, Compressed gas

Simple Asphyxiant

Skin Corrosion/Irritation, Category 1B

Serious Eye Damage/Eye Irritation, Category 1

Germ Cell Mutagenicity, Category 1B

Carcinogenicity, Category 1B

Specific Target Organ Toxicity (single exposure), Category 3









GHS Signal Word:

Danger

GHS Hazard Phrases:

Flammable gas.

Containers gas under pressure; may explode if heated.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause drowsiness or dizziness.

May cause genetic defects.

May cause cancer.

May displace oxygen and cause rapid suffocation.

GHS Precautionary Phrases:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with

water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Revision: 03/06/2019

IF exposed or concerned: Get medical attention/advice. Immediately call a POISON CENTER or doctor/physician.

Specific treatment see label.

Wash contaminated clothing before reuse.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

GHS Storage and Disposal

Store container tightly closed in well-ventilated place.

Phrases:

Store locked up.

Protect from sunlight and store in well-ventilated place.

Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute

Otential Health Ellet

Referenced above.

and Chronic):

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	30.0 -60.0 %
67 - 64-1	Acetone {2-Propanone}	15.0 -40.0 %
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	7.0 -13.0 %
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	0.5 -1.5 %
929-06-6	2-(2-Aminoethoxy) ethanol	0.1 -1.0 %

Additional Chemical Information Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms Of

Exposure:

Note to Physician:

See Potential Health Effects.

Revision: 03/06/2019

5. FIRE FIGHTING MEASURES

Level 2

Flash Pt:

-17.8 C (0.00 F) Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits:

LEL: N.D.

UEL: N.D.

Autoignition Pt:

N.D.

Suitable Extinguishing Media:

Use carbon dioxide, dry powder, or alcohol resistant foam.

Unsuitable Extinguishing Media: Do not use straight streams of water. If water is used, use a water spray or fog.

Fire Fighting Instructions:

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to

intense heat or flame.

Flammable Properties and

Hazards:

Danger! Flammable. Keep away from heat, sparks, flame, and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity

that may be generated by synthetic clothing and other sources.

Hazardous Combustion

Products:

Carbon monoxide, carbon dioxide, hydrogen chloride, chlorine, phosgene

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:

Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Revision: 03/06/2019

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

Precautions To Be Taken in Storing:

Store in a cool place in original container and protect from sunlight. Exposure to high temperatures or prolonged exposure to sun may cause can to leak or swell. Do not store near flames or at elevated temperatures.

Keep container tightly closed when not in use - Tetrahydrofuran may form peroxides when exposed to air.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS # Che	emical Name	Jurisdiction	Recommended Exposure Limits	Notations
109-99-9 Tetrah Diethylene oxide;	nydrofuran {THF; 1,4-Epoxybutane}	ACGIH TLV	TLV: 50 ppm STEL: 100 ppm	
		OSHA PELs	PEL: 200 ppm	
67-64-1 Aceton	e {2-Propanone}	ACG/H TLV	TLV: 500 ppm STEL: 750 ppm	
		OSHA PELs	PEL: 1000 ppm	
7664-41-7 Amm Ammonia; R-717}	onia {Anhydrous	ACGIH TLV	TLV: 25 ppm STEL: 35 ppm	
		OSHA PELs	PEL: 50 ppm	

Type):

Respiratory Equipment (Specify For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved self-contained breathing apparatus or powered air supply respirator or loose fitting hood.

> For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

Eye Protection: Chemical goggles, or face shields are recommended to safeguard against potential eye contact,

irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical

contact to the face and eyes.

Protective Gloves: Wear gloves with as much resistance to the chemical ingredients as possible. Laminate film

gloves offer the best protection. Consult your glove supplier for additional information. Gloves

contaminated with product should be discarded and not reused.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment, such as

impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other

protective equipment that cannot be decontaminated, such as gloves or shoes.

Engineering Controls

(Ventilation etc.):

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. If the work area is not well ventilated, DO NOT use this product. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas.

Whenever possible, use outdoors in an open air area. If using indoors open all windows and

Revision: 03/06/2019

doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering – STOP –

ventilation is inadequate. Leave area immediately and move to fresh air.

Work/Hygienic/Maintenance

Practices:

Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Facilities storing or handling this material should be equipped with an emergency eyewash and

safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:

[X] Liquid

[] Solid

Appearance and Odor:

Off-white opaque viscous liquid

Aromatic with ammona odor

Odor threshold not determined

pH:

N.D.

[X]Gas

Melting Point:

N.D.

Boiling Point:

N.D.

Flash Pt:

-17.8 C (0.00 F) Method Used: Setaflash Closed Cup (Rapid Setaflash)

Evaporation Rate:

ND

Flammability (solid, gas):

Flash Point is for liquid contents.

Explosive Limits:

LEL: N.D.

UEL: N.D.

Vapor Pressure (vs. Air or mm

Hg):

Vapor Density (vs. Air = 1):

N.D.

Specific Gravity (Water = 1):

.8534

N.D.

Density:

7.101 LB/GL

Solubility in Water:

N.D.

Octanol/Water Partition

N.D.

Coefficient:

Percent Volatile:

95.68 % by weight.

VOC / Volume:

49.6000 % WT

Autoignition Pt:

N.D.

Decomposition Temperature:

N.D.

Viscosity:

N.D.

10. STABILITY AND REACTIVITY

Stability:

Unstable []

Stable [X]

Incompatibility - Materials To

Conditions To Avoid - Instability: Stable

Bases, oxygen, sodium, potassium, strong oxidizers, reactive metals, strong acids

Avoid:

Hazardous Decomposition or

Carbon monoxide, carbon dioxide

Byproducts:

Possibility of Hazardous

Will occur []

Will not occur [X]

Reactions:

Conditions To Avoid - HazardousWill not occur.

Reactions:

Revision: 03/06/2019

11. TOXICOLOGICAL INFORMATION

Toxicological Information:

This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.

CAS# 109-99-9:

Other Studies:, TDLo, Oral, Rat, 26280. mg/kg.

Result:

Liver: Tumors.

Kidney, Ureter, Bladder: Kidney tumors.

- Toxicologist., Soc. of Toxicology, Inc., 475 Wolf Ledge Parkway, Akron, OH 44311, Vol/p/yr:

60,286, 2001

CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay). Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415,

Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

Chronic Toxicological Effects:

This product has not been tested as a whole.

Carcinogenicity/Other

ACGIH A4 - Not Classifiable as a Human Carcinogen.

Information:

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	n.a.	n.a.	n.a.	n.a.
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	n.a.	n.a.	n.a.	n.a.
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	n.a.	n.a.	n.a.	n.a.
929-06-6	2-(2-Aminoethoxy) ethanol	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: This product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose in accordance with all applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name:

Aerosols, flammable, corrosive

DOT Hazard Class:

2.1(8)

FLAMMABLE, CORROSIVE

UN/NA Number:

UN1950





Page: 7

Revision: 03/06/2019

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:

UN Number:

1950

Hazard Class:

2.1(8) - FLAMMABLE,

TDG Classification:

CORROSIVE

Additional Transport

Information:

The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (S	uperfund Amendments and Reauthorization Act	of 1986) Lists		
CAS# 109-99-9	Hazardous Components (Chemical Name) Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	S. 302 (EHS) No	S. 304 RQ Yes 1000 LB	S. 313 (TRI) No
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No	No	No
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	Yes 500 LB	Yes 100 LB	Yes
929-06-6	2-(2-Aminoethoxy) ethanol	No	No	No
CAS#	Hazardous Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	Yes: Part 5	No	Yes
67-64-1	Acetone {2-Propanone}	No	No	Yes
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No	Yes - 134.z.20	Yes
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	No	Yes - 53.	Yes
929-06-6	2-(2-Aminoethoxy) ethanol			Yes
CAS#	Hazardous Components (Chemical Name)	Other US EPA or	State Lists	
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}		o; CWA NPDES: No; R; CA PROP.65: No	TSCA: Yes -
67 - 64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No		
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No		
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	CAA HAP,ODC: N	o; CWA NPDES: Yes	; TSCA: Yes -
929-06-6	2-(2-Aminoethoxy) ethanol	CAA HAP,ODC: N	o; CWA NPDES: No; PAIR; CA PROP.65: N	

Canadian WHMIS Classification:

No data available.

Page: 8

Revision: 03/06/2019

Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

16. OTHER INFORMATION

Revision Date:

03/06/2019

Preparer Name:

W.M. Barr EHS Dept (901)775-0100

Additional Information About

No data available.

This Product:

Company Policy or Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with

applicable federal, state and local laws and regulations.